println!

println!

```
println!(“Hello world!”);
```

println!

```
println!(“Hello world!”);
```

Formatting

```
println!(“My name is {} and I’m {}”, “Alex”, 29);
```

println!

```
println!(“Hello world!”);
```

Formatting

```
println!(“My name is {} and I’m {}”, “Alex”, 29);
```

Expressions

```
println!("a + b = {}", 3+6);
```

println!

```
println!(“Hello world!”);
```

Formatting

```
println!(“My name is {} and I’m {}”, “Alex”, 29);
```

Expressions

```
println!("a + b = {}", 3+6);
```

Positional arguments

```
println!("{0} has a {2} and {0} has a {1}", "Alex", "cat", "dog");
```

println!

```
println!(“Hello world!”);
```

Formatting

```
println!(“My name is {} and I’m {}”, “Alex”, 29);
```

Expressions

```
println!("a + b = {}", 3+6);
```

Positional arguments

```
println!("{0} has a {2} and {0} has a {1}", "Alex", "cat", "dog");
```

Named arguments

```
println!("{name} {surname}", surname="Smith", name="Alex");
```

println!

Printing traits

```
println!(“binary: {:b}, Hex: {:x}, Octal: {:o}”, 5, 5, 5);
```

println!

Printing traits

```
println!(“binary: {:b}, Hex: {:x}, Octal: {:o}”, 5, 5, 5);
```

Debug

```
println!("Array {:?}", [1, 2, 3]);
```